

| | |
|---------------------------|---|
| Shape: | Double D or Round shape |
| Dimension: | 12300mm×2500mm×3800mm (The exact size depends on the final design and requirements from customers.) |
| Total Volume (m3): | 40 m ³ |
| Compartments: | 3 15,000L-15,000L-10,000L |
| Tanker Body Material: | 5 mm thickness, Q345 |
| End Plate: | 6 mm thickness, Q345 |
| Wave board: | 5 mm thickness, Q345 |
| Manhole Cover: | 3pcs, 500mm(diameter), Europe type Aluminum alloy material |
| Bottom Valve: | 3pcs, 4 inches Europe type subsea valve |
| Discharging Valve: | 3pcs, 2.5 inches Europe type outlet |
| Discharging Pipe: | 2.5" rubber hose, 2 pcs , 6m/each unit |
| Pump System: | Optional |
| Walkway: | Anti-skid walkway on top of the tank, with foldable handrail on both sides of the manhole covers. |
| Ladder: | Anti-skid access ladder fitted at front/back head of the tank. |
| Main Beams: | Welded design, Q345 |
| Axle: | 3 axles, 13 tons |
| Landing Gear: | JOST E100, double speed type |
| King Pin: | JOST 2.0 or 3.5 inches bolt-in king pin |
| Suspension: | Mechanical suspensions |
| Pneumatic Braking System: | WABCO RE 6 relay valve; Spring brake chamber (TKL brand); one piece of 45L air tank |
| Rim: | 9.0-22.5, 13pcs |
| Tire: | Triangle brand 12R22.5, 13pcs |
| ABS: | Optional |
| Accessories: | One standard tool box, one spare tire carrier |
| Shipping Terms: | By bulk vessel |

