| Product Parameter | |
|------------------------|---|
| Dimension(mm): | 12500x2500x3050mm |
| Trailer Sides: | 1000mm height (Customized by you) |
| Loading capacity(ton): | 60T |
| Axles: | 3 axles, 13T/16T, FUWA/ BPW Brand |
| Tire: | 12 units, 12.00R22.5 or 315/80R22.5 |
| Suspension: | Mechanical/Bogie/Airbag suspension |
| King Pin: | JOST brand 2.0 or 3.5 inch (bolted or welded) |
| Landing Gear: | JOST brand C200T |
| Bottom Platform: | 3mm-thick checkered plate |
| Brake Chamber: | WABCO RE 6 relay valves; T30/30+T30 spring braking chamber (TKL brand), 45L air tank |
| Twist Locks: | 4,8,12 sets (lifting or screw type) |
| Valve: | WABCO valve (specially intended for oversea market) |
| ABS: | Optional |
| Electric system: | One unit of 24V 7-pin ISO standard socket; with brake light, turn light, reverse light, side light, reflector, fog light; one set of 6-pin standard cable |
| Painting: | S.A.2.5standard sandblasting; Two coat of anti-corrosion prime; one coat of finish painting |

One tool box; one set of standard tools.

Accessory:



