

Product Parameter	
Dimension(L*W*H):	11500*2500*3600 (mm) (Customized Sizes or Designed according to customers' needs)
Compartments:	3 (Customizable) 15,000L-15,000L-12,000L
Shape:	Square, Round (Customizable)
Valid Volume (L):	42000 (Customizable)
Body Steel Material:	6mm aluminum alloy 5182
End Plates:	6mm aluminum alloy 5182
Resistant Wave Plates:	5mm aluminum alloy 5182
Partition Chamber Plates:	5mm aluminum alloy 5182
Pneumatic Control system:	1set Pneumatic Control combined switch 1unit emergency switch
Discharging Pipe:	2 pcs, 6m/pc
Kingpin:	JOST 3.5" /2.5" bolt-in type
Landing gear:	JOST brand 19" Double-speed
Tires:	11R22.5 /12R22.5/315/85R22.5
Axle:	FUWA/BPW/ZY or other Brands
Suspension:	Mechanical suspension with springs/Air suspension/Bogie suspension
Brake system:	Dual line with WABCO brand Re-6 emergency relay valve, T30/30 air chamber, 45L air tanks
Electric system:	One unit of 24V 7-pin ISO standard socket; with brake light, turn light, reverse light, side light, reflector, fog light; one set of 6-pin standard cable
With safety devices:	the manhole is an explosion-proof large cover. The bottom outlet of the tank is equipped with an emergency shut-off valve.

