

Product Parameters:	
Dimension(L*W*H):	12000*2500*3650 (mm) (Customized Sizes or Designed according to customers' needs)
Compartments:	4 (Customizable) 10,000L-10,000L-10,000L-10,000L
Shape:	Square, Round (Customizable)
Valid Volume (L):	40000 (Customizable)
Body Steel Material:	Q345B / 5mm
End Plates:	Q345B / 6mm, by punching
Resistant Wave Plates:	Q345B / 5mm
Partition Chamber Plates:	Q345B / 6mm
Manhole Cover:	4pcs, 500mm(diameter), Europe type Aluminum alloy material
Bottom Valve:	4pcs, 4 inches Europe type subsea valve
Discharging Valve:	4pcs, 2.5 inches Europe type outlet
Pneumatic Control system:	1set Pneumatic Control combined switch and 1unit emergency switch
Discharging Pipe:	2 pcs, 6m/pc
Kingpin:	JOST 3.5" /2.5" bolt-in type
Landing gear:	JOST brand 19" Double-speed
Tires:	11R22.5 /12R22.5/315/85R22.5
Axle:	FUWA/BPW/ZY or other Brands
Suspension:	Mechanical suspension with springs/Air suspension/Bogie suspension
Brake system:	Dual line with WABCO brand Re-6 emergency relay valve, T30/30 air chamber, 45L air tanks
Electric system:	One unit of 24V 7-pin ISO standard socket; with brake light, turn light, reverse light, side light, reflector, fog light; one set of 6-pin standard cable

